PLN STONE WOOL SLABS









Code certification CE: MW - EN 13162 - T3- MU1



TECHNICAL SPECIFICATION

Slabs made from ISOVER stone wool. The boards are obtained by melting the mineral raw materials in a furnace, fiberising the melt by REX process, spraying a a binder and adding mineral oils for protection against dust and water repellence.

The mineral fibers mat is processed into boards which are packaged on the production line.

APPLICATION

ISOVER PLN slabs are used for thermal, acoustic and fire insulation in civil and industrial buildings:

- curtain walls
- partition walls with specified fire resistance performances
 PLN slabs can also be used in marine applications.

PACKAGING, TRANSPORT, WAREHOUSING

ISOVER PLN slabs are packaged in PE foil. The slabs must be transported and stored avoiding contact with water, or other damage.

BENEFITS

- high thermal insulation performance (low thermal conductivity)
- fire safety non combustible material
- excellent acoustic properties (high absorption coefficient)
- easy to handle, non-toxic
- low vapour flow resistance
- long term resistance in vertical position
- environment friendly and hygienic
- completely hydrophobic is made water repellent
- long life span and time-stable properties
- resistant to mould, mildew, rodents and insects
- chemically neutral, non-corrosive
- easy workability can be cut, drilled etc.

CERTIFICATES, STANDARDS, APPROVALS

- EC Certificate: 1840-DPC-99/91/EC/0114-07
- ISO 9001, ISO 14001, OHSAS 18001
- EC Type Marine Certificate: 11433/C0 EC

TEHNICAL PARAMETERS

| PARAMETER | UNIT | VALUE | | | |
|---|----------|--------|--|--|--|
| THERMAL INSULATION PROPERTIES | | | | | |
| Declared thermal conductivity λ_D | W/(m K) | 0,034 | | | |
| FIRE SAFETY PROPERTIES | | | | | |
| Reaction to fire | - | A1 | | | |
| OTHER PROPERTIES | | | | | |
| Maximum temperature for use | °C | 200 | | | |
| Melting temperature | °C | ≥ 1000 | | | |
| Air flow resistivity AFr | kPa s/m² | >5 | | | |
| Water vapour diffusion resistance factor µ MU | - | 1 | | | |

DIMENSIONS AND PACKAGING

| Product | Thickness (mm) | Length * width (mm) | Dimension per package (m²/package) | Declared thermal resistance R _D (m ² .K/W) |
|---------|----------------|---------------------|------------------------------------|--|
| PLN 50 | 50 | 1000 x 600 | 4,80 | 1,45 |
| PLN 60 | 60 | 1000 x 600 | 3,60 | 1,75 |
| PLN 80 | 80 | 1000 x 600 | 2,40 | 2,35 |
| PLN 100 | 100 | 1000 x 600 | 2,40 | 2,90 |



02.10.2012. Declared characteristics are valid at the date of publishing. The manufacturer reserves the right to change them.

